

EXCEREX 40800(T) Data Sheet

Low-Molecular-Weight Polyolefins

Physical properties

Item	Unit	Testing Method	Typical Value
Molecular Weight	-	Viscometric Method	4,000
Density	kg/m ³	JIS K7112	980
Acid Value	KOH mg/g	JIS K0070	-
Crystallinity	%	X-ray Diffractometry	-
Melting Point	°C	DSC	128
Softening Point	°C	JIS K2207	135
Hardness (Penetration Test)	10-1mm	JIS K2207	1↓
Melt Viscosity	mPa·s cp	Brookfield Type Viscometer(140°C)	750

Notes: These values are not specified.

The information contained herein is, to the best of our knowledge, accurate and reliable. However, since the actual conditions of use(s) of our products are beyond our control, IT IS THE USER'S RESPONSIBILITY TO ASSUME ALL RISKS OF SUCH USE(S) FOR SPECIFIC APPLICATIONS. Mitsui Chemicals makes no guarantees of results and assumes no liability in connection with its recommendations or suggestions. Nothing contained herein shall be construed as a recommendation for use in violation of any patents or of applicable laws and regulations. SAMPLES ARE PROVIDED WITHOUT ANY WARRANTIES, EXPRESSED OR IMPLIED.