

Product name	Solvent	Vis (GH/25°C)	NV (%)	AV (Vanish)	Color number (Hassen)	Compatibility cc/g		Resin type to be used with	Applications	Features
						XY(20°C)	MS(20°C)			
60R	iso-BuOH	E-L	50	1>	30>	(ASTM) 4~8	5~10	Acrylic, Alkyd	Metal	Low temperature curing
62	XY /3 iso-BuOH/7	Q-V	60	1>	30>	20<	10~15	"	"	Standard type
62E	XY /1.5 iso-BuOH/8.5	M-U	60	1>	30>	20<	10~20	"	"	Good compatibility
360	XY /1.5 iso-BuOH/8.5	T-X	60	1>	(GH) 1>	-	4~15	"	"	Low temperature curing, Good compatibility
165	XY /2 iso-BuOH/8	M-S	60	1>	30>	-	6~16	"	"	"
166-60	iso-BuOH	R-W	60	1>	50>	-	1~10	"	"	"
169	XY /1 iso-BuOH/9	U-Y	60	1>	50>	-	5~15	"	"	Good corrosion resistance
2061	iso-BuOH/7 MeOH /3	Y-Z ₂	75	1>	30>	∞	-	"	"	Good corrosion resistance, Good stability

Vis: Viscosity NV: Non-volatile AV: Acid value XY: Xylene n-BuOH: n-Butanol
MeOH: Methanol iso-BuOH: iso-Butanol MeOH: Methanol